HEWLETT-PACKARD

HP LaserJet Series II

Desktop Office Printer

Data Sheet

Features

Publication-quality laser printing for the office

- High resolution text and graphics
- Prints up to eight pages per minute
- Memory expansion capability
- Selection of high-quality fonts
- Extensive software support
- LaserJet PLUS printer compatibility
- Excellent paper handling and ease of use

The HP 33440A LaserJet Series II printer is designed for business and technical professionals requiring a quiet, high-resolution printer. It is well-suited for applications such as general, technical and legal word processing, spreadsheets, reports, forms, and desktop publishing. Printing at up to eight pages per minute, it can be used by one or several PC users and offers memory expansion capability to accommodate several users or more complex applications.

Publication-quality Printing

The LaserJet Series II printer prints at 300 × 300 dotsper-inch resolution, providing crisp, easy-to-read text and graphics. The SX engine design and toner composition ensure dense, even coverage throughout each page. A wide selection of font cartridges and downloadable soft fonts is available to complement the printer's built-in fonts and two font cartridge slots. Professional-looking documents can be produced in a variety of typefaces, styles, and point sizes.

Extensive Software Support

With HP's industry-standard PCL printer language built into the printer, the LaserJet Series II printer works with more than 700 software packages. It is compatible with the same software, font cartridges and soft fonts that work with the original LaserJet, LaserJet PLUS, and LaserJet 500 PLUS printers. The printer is equipped with a Centronics parallel interface and an RS-232-C/RS-422-A serial interface for compatibility with most PCs.



Excellent Paper Handling

The LaserJet Series II printer holds 200 sheets of paper in a letter-, legal-, A4-, or B5-sized input tray, and stacks up to 100 sheets in the correct order in the output tray. The printer handles envelopes using the manual feed feature or an envelope tray accessory. Heavier paper (up to 35 lbs), labels and overhead transparencies can also be used.

Easy to Use

The 16-character LCD control panel on the LaserJet Series II printer lets the user configure and customize the printing environment. For example, the number of copies, number of lines per page, type of interface and primary font can be selected from the control panel.

The single-component, easy-to-replace toner cartridge prints approximately 4000 pages of normal text. The print drum is part of each toner cartridge, keeping print quality high at a low printing cost (approximately 3 cents per page, excluding paper costs).

Specifications

Printing Process

Dry type electrophotography

Printing Speed

First page less than 16 seconds after receipt of data. Subsequent pages at 8 pages per minute — job throughput is application and system dependent.

Warm-up Time

Less than 30 seconds from cold turn on.

Text and Graphics

Text Resolution

 300×300 dots-per-inch

Graphics Resolution

 300×300 dots-per-inch

Printing Format

Print Orientation:

Portrait (printing across the width of the page) Landscape (printing across the length of the page)

Internal Fonts

	Courier Medium*	Courier Bold	Compressed Line Printer
Orientation	Portrait Landscape	Portrait Landscape	Portrait Landscape
Symbol Set**	Roman-8 IBM-US IBM-DN ECMA-94	Roman-8 IBM-US IBM-DN ECMA-94	Roman-8 IBM-US IBM-DN ECMA-94
Spacing	Fixed	Fixed	Fixed
Pitch	10 cpi	10 срі	16.66 cpi
Point Size	12 point	12 point	8.5 point
Style	Upright	Upright	Upright
Stroke Weight	Medium	Bold	Medium
Typeface	Courier	Courier	Line printer

^{*}The Courier Portrait (medium) font is the printer's factory default font. This font is used unless you: select another default using the control panel; send a font selection command to request a font in place of the default; or a cartridge with a default font is installed.

Paper

Paper Type

Single-sheet copier paper

NOTE: The LaserJet Series II printer is designed for use with high-quality copier bond paper. To obtain the clearest, sharpest images, paper manufactured for photocopiers such as Canon NP or Xerox 4024 should be used. Most cotton bond paper also works well on the LaserJet Series II printer. The printer can also accommodate a wide variety of special application paper, such as label stock, colored and pre-printed paper, as well as overhead transparency film designed for laser printers. It is strongly recommended that all paper be tested before purchasing.

Paper Weight

60 to 135 g/m² (16 to 35 lbs)

Paper Size

Letter (8.5 \times 11 in.) Legal (8.5 \times 14 in.)

A4 (European) $(210 \times 297 \text{ mm})$

Executive $(7.5 \times 10.5 \text{ in.})$

NOTE: Best results will be obtained if paper is stored and used within the listed ranges.

Temperature: 17 to 23 degrees C (63 to 73 degrees F)

Relative Humidity: 40 to 50%

Paper Handling

200-sheet input paper tray and 100-sheet output paper tray

Correct order output

Reverse order output through the face-up output paper tray only (20 sheet)

Manual feed for envelopes, heavier paper stock and odd size paper

Printable Surface (Portrait)

Width	Std.	Legal	A4	Exec.
inches	8.0	8.0	7.8	6.75
mm	203	203	198	171
Length				
inches	10.6	13.6	11.3	10.1
mm	269	345	287	257
Length inches	10.6	13.6	11.3	10.1

Control Panel

Buttons: on line, continue/reset, print fonts/test, form feed, enter/reset menu, menu, +, Indicators: ready, manual

Interfaces

Centronics Parallel, RS-232-C/422 (300–19.2 Kbytes baud)

Buffer Size

395 Kbytes of user memory standard

^{**}These additional symbol sets can be used with internal fonts: ISO 2, 4, 6, 10, 11, 14, 15, 16, 17, 21, 25, 57, 60, 61, 69, 84, 85, HP Spanish, and HP German. ISO denotes International Standards Organization symbol sets, primarily for use in Europe or for printing non-English characters.

Environmental Ranges

Temperature (Printer and Toner Cartridge)

Operating: 10 to 32.5 degrees C (50 to 91 degrees F) Storage: 0 to 35 degrees C (32 to 95 degrees F)

Humidity

Operating: 20 to 80% RH Storage: 10 to 80% RH

Altitude

Operating: 0 to 2500 m (0 to 8200 ft) Storage: 0 to 15 000 m (1 to 49 200 ft)

Acoustics (average sound pressure measured at 1 m per ISO 7779)

Printing

Maximum sound power level-Lwa: 6.3 bels(A) Maximum sound pressure level-Lpa: 50 dB(A)

Standby:

Maximum sound power level-Lwa: 5.3 bels(A) Maximum sound pressure level-Lpa: 40 dB(A)

Power Requirements

Source: 100 to 115 volts, 220 to 240V (+10%, -10%)

Frequency: 50 or 60Hz Consumption at 115VAC: Printing: 870 Watts maximum Standby: 170 Watts (nominal)

Physical Specifications

Height: 22.8 cm (8.5 in.) Width: 45.4 cm (18.0 in.)

Depth (body only): 48.2 cm (19.0 in.)

Depth (with tray): 81.5 cm (24.5 in. all trays but legal

27.0 in.)

Net Weight: 22.4 kg (50.0 lbs)

Product Certifications

UL 478 listed; CSA 22.2 154 Certified; Complies with IEC 380 and IEC 435; FCC level B; VDE 0871B, VDE 0836, IEC-TC76 and VBG 93; BRH Certified Class 1 Laser Product (safe for office/EDP use).

Estimated Typical Usage

Up to 5000 pages per month

Interface and Cable Requirements

System	Interface	HP Cable	Cable Length
HP 110	Serial	92221P	1.5 m (5.0 ft)
HP 150	Serial	17255D	1.0 m (3.3 ft)
HP 150	Serial	92219G	3.8 m (12.5 ft)
HP 150	Serial	13242-60010	5.0 m (16.7 ft)
HP 150	Parallel	13242D	2.0 m (6.6 ft)
HP Vectra	Serial	24542G	3.0 m (10.0 ft)
HP Vectra	Parallel	24542D	2.0 m (6.6 ft)
HP Vectra	Parallel	92219K	2.7 m (9.0 ft)
Apple IIe	Serial	17355M	2.3 m (9.0 ft)
DEC Rainbow	Serial	17355M	2.3 m (9.0 ft)
IBM PC, PC/XT	Serial	92219J	5.0 m (16.0 ft)
IBM PC/XT, PC/AT	Parallel	24542D	2.0 m (6.6 ft)
IBM PC, PC/XT, PC/AT	Parallel	92219K	2.7 m (9.0 ft)

Ordering Information

Standard Unit

33440A LaserJet Series II printer, includes Getting Started Manual, User's Manual, 512K RAM memory (up to 395K user memory), Parallel & RS-232-C/422 interface, EP-S toner cartridge, 200-sheet letter-size input paper tray

Accessories

33443A	1 Mbyte memory board
33444A	2 Mbyte memory board
33445A	4 Mbyte memory board
92295A	Black toner cartridge (EP-S)
92295B	Letter-size paper tray $(8.5 \times 11 \text{ in.})$
92295C	Legal-size paper tray $(8.5 \times 14 \text{ in.})$
92295D	A4-size paper tray $(210 \times 297 \text{ mm})$
92295E	Executive-size paper tray $(7.25 \times 10.5 \text{ in.})$
92295R	Replacement top cover for B, D, & E
	paper trays
92295S	Replacement top cover for C paper tray
92295F	LaserJet Series II envelope tray (maximum o
	15 envelopes; available in the United States

and Canada only)

Supplies

Soft Fonts*	
33411AC	Tms/Helv Base, ASCII, HP 150 format only
33411AD	Tms/Helv Base, Roman-8, HP 150 format only
33411AE	Tms/Helv Supp, ASCII, HP 150 format only
33411AF	Tms/Helv Supp, Roman-8, HP 150 format only
33411DA	Letter Gothic Family, HP 150 format only
33411EA	Prestige Elite Family, HP 150 format only
33412AC	Tms/Helv Base, ASCII, 5.25 in. disc
33412AD**	Tms/Helv Base, Roman-8, 5.25 in. disc
33412AE	Tms/Helv Supp, ASCII, 5.25 in. disc
33412AF**	Tms/Helv Supp, Roman-8, 5.25 in. disc
33412DA**	Letter Gothic Family, 5.25 in. disc
33412EA**	Prestige Elite Family, 5.25 in. disc
33412RA	ITC Garamond®, ASCII, 5.25 in. disc
33412RB	ITC Garamond, Roman-8, 5.25 in. disc
33412SA	Century Schoolbook®, ASCII, 5.25 in. disc
33412SB	Century Schoolbook, Roman-8, 5.25 in. disc
33412TA	Zapf Humanist™, ASCII, 5.25 in. disc
33412TB	Zapf Humanist, Roman-8, 5.25 in. disc
33412UA	Headline Typefaces™ 1, ASCII, 5.25 in. disc
33412UB	Headline Typefaces 1, Roman-8, 5.25 in. disc
33412AG	Helv Headlines, 5.25 in. disc
33407B	FontLoad™, 5.25 in. disc (utility)

NOTE: 33412AD and 33412AF also include the ASCII characters contained in 33412AC and 33412AE, respectively.

^{*}Soft fonts are licensed for use with up to three printers.

^{**}Also available with corporate license for use with up to 100 printers (option 100).

Font Cartridges 92286A Courier Tms Proportional 1 92286B 92286C International 1 92286D Prestige Elite Letter Gothic 92286E 92286F Tms Proportional 2 92286G Legal Elite Legal Courier 92286H 92286I Math Elite 92286K Math TMS Courier P & L 92286L 92286M Prestige Elite P & L Letter Gothic P & L 92286N 92286P TmsRmn P & L 92286Q Memo 1 92286R Presentations 1 92286T Tax 92286U Forms Portrait Forms Landscape 92286V Bar Code 3-of-9/OCR-A 92286WI 92286X EAN/UPC/OCR-B Courier PC 1 92286Y Microsoft® 1A 92286Z

LaserJet Series II and LaserJet 2000 printers only:

92290S1 Courier Document 1 92290S2 Tms/Helv Report 1

NOTE: For font print samples and other font information, ask your HP Dealer or Sales Representative for the LaserJet Printer Supplies and Accessories brochure, part number 5956-4252.

Printer supplies are available at authorized HP dealers or through HP's Direct Marketing Operation in the U.S. (800-538-8787); in California call (408) 738-4133 collect.

Manuals

33440-90908	LaserJet Series II Getting Started Manual
33440-90901	LaserJet Series II User's Manual
33440-90905	LaserJet Series II Technical Reference
	Manual

In the **U.S.A.**, call toll-free **1-800-752-0900** for the sales office or dealer nearest you. Outside the U.S.A., contact: **Canada** — 6877 Goreway Drive, Mississauga, Ontario, Canada, L4V 1M8. **Europe** — 150 Route du Nant-d'Avril, P.O. Box CH-1217 Meyrin 2, Geneva, Switzerland. **Japan** — Yokogawa-Hewlett-Packard Ltd., 29-21, Takaido-Higashi 3-chome, Suginami-ku, Tokyo 168. **Australia/New Zealand** — 31-41 Joseph Street, Blackburn, Victoria 3130, Melbourne, Australia. **Far East** — 47/F China Resources Bldg., 26 Harbour Road, Wanchai, Hong Kong. **Latin America** — Monte Pelvux No. 111, Lomas de Chapultepec, 11000 Mexico D.F., Mexico. **Elsewhere in the world** — Hewlett-Packard Intercontinental, 3495 Deer Creek Road, Palo Alto, CA 94304, U.S.A.

Apple Macintosh is a product of Apple Computer, Inc. Century Schoolbook is a registered trademark of Kingsley-ATF. FontLoad is a trademark of Hewlett-Packard. Headline Typefaces is a trademark of Bitstream, Inc. IBM PC is a product of International Business Machines Corporation. ITC Garamond is a registered trademark of International Typeface Corporation. Microsoft is a U.S. registered trademark of Microsoft, Inc. PCL is a trademark of Hewlett-Packard's printer Command Language. Zapf Humanist is a trademark of Bitstream, Inc.

Technical information in this document is subject to change without notice. Copyright @ Hewlett-Packard Co. 1988

